

XVR

PDR-2G604



Technical Specifications

Recording Bandwidth

Inputs	16Mbps~128Mbps
out	216Mbps
Analog video-input	32CH inputs

Live

IP Video Input	4ch(only IP up to 32ch)
Composite Video Input	up to 36ch (Analog video + IP video)

Recording and Playback

Compression	Audio: G.711a Video : H.264/H.265
Display resolution	Analog: 5MP-Lite:20fps/4MP-Lite:30 fps/1080P/720P/960H:30fps IP: 5MP/4MP/3MP1080P/720P
Speed	Analog : 5MP-Lite:15fps (each ch)/4MP-Lite:20fps(each ch)/ 1080P:30fps(each ch)/720P:PAL:25fps(each ch)/NTSC:30fps(each ch) IP : PAL:25fps(each ch)/NTSC: 30fps(each ch)

AI	PID - Perimeter Intrusion Detection LCD - Line Crossing Detection PD&VD - Human&Vehicle Detection FD - Face Detection FR - Face Recognition
----	---

Event	MD(Sensitivity Level 1~8) Videlo loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MP-lite: 480fps (Max 16CH playback) 4MP-lite: 720fps (Max 16CH playback) 1080P:480fps (Max 16CH playback) 720P:1080fps (Max 16CH playback)

UI / Monitoring

Local	UI5.0
WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Mobile viewer	CybVu
Interface	
P/W Reset	Factory Reset : Press 10 seconds

Monitors

BNC	1 (704*576)
VGA	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1(1024*768,1280*720,1280*1024,1440*900,1920*1080,2560*1440(2K),3840*2160(4K)
Ethernet	2 RJ45 100/1000 Base-T
USB	USB2.0*1(front) USB3.0*1+(rear)
Audio	8 in / 1 out
HDD	4 SATA HDD, Up to 12 TB capacity for each disk
ESATA	1
RS485	1
Alarm Input/out	16 in /1 out

General

OSD Language	English/French/Spanish/Portuguese/German/Italian/Greek/Danish/Finnish/Russia/ Hebrew/Turkish/Bulgarian/Arabic/Korean/Japanese/Thai/Hindi/Romanian/Dutch/ Polish
Dimension (WxDxH)	378*326*66mm
Input Voltage/Current	DC12V/5A
Power consumption	21W
Temperature/Humidity	Temperature : -10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH